ARTIFACT SHEET

Enter a	artifact number below. Artifact number is application number 🕂
artifac	t type code (see list below) + sequential letter (A, B, C). The first
artifac	t folder for an artifact type receives the letter A, the second B, etc
Examp	oles: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB
•	oles: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB
Indicat	te quantity of a single type of artifact received but not scanned. Create
	lual artifact folder/box and artifact number for each Artifact Type.
$\lceil \cdot \rceil$	CD(s) containing:
, لـــا	Computer program listing
	Doc Code: Computer Artifact Type Code: P
	Pages of specification
	And/or sequence listing
	And/or table
•	Doc Code: Artifact Artifact Type Code: S
(Content unspecified or combined
	Doc Code: Artifact Artifact Type Code: U
	a tia () at B
	Stapled Set(s) Color Documents or B/W Photographs
L	Doc Code: Artifact Type Code: C
<u> </u>	Microfilm(s)
] [Doc Code: Artifact Artifact Type Code: F
	Doc Code : Addition - Addition Type Code : 1
	Video tape(s)
	Doc Code: Artifact Artifact Type Code: V
	Model(s)
	Doc Code: Artifact Type Code: M
	Bound Document(s)
	Doc Code: Artifact Type Code: B
	Confidential Information Disclosure Statement or Other Documents
	Marked Proprietary, Trade Secrets, Subject to Protective Order,
	Material Submitted under MPEP 724.02, etc. Doc Code: Artifact Artifact Type Code: X
/	
$\overline{}$	Other, description: US postent
~	Doc Code: Artifact Artifact Type Code: Z

The United States America

The Commissioner of Patents and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America for the term set forth below, subject to the payment of maintenance fees as provided by law.

If this application was filed prior to June 8, 1995, the term of this patent is the longer of seventeen years from the date of grant of this patent or twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

If this application was filed on or after June 8, 1995, the term of this patent is twenty years from the U.S. filing date, subject to any statutory extension. If the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121 or 365(c), the term of the patent is twenty years from the date on which the earliest application was filed, subject to any statutory extension.

Luce Celman
Commissioner of Patents and Trademarks
Pandra Morty



US005639119A

United States Patent [19]

Plate et al.

[11] Patent Number:

5,639,119

[45] Date of Patent:

Jun. 17, 1997

[54] FORKLIFT STABILIZING APPARATUS

[75] Inventors: John R. Plate, Milwaukee; J. Scott Bargenquast, Saukville; Terry A.

Weber, Greenfield, all of Wis.

[73] Assignee: Trak International, Inc., Port

Washington, Wis.

[21] Appl. No.: 350,216

[22] Filed: Dec. 5, 1994

Related U.S. Application Data

[62]	Division o	f Ser. No. 986,145, Dec. 4, 1992,	abandoned.
[51]	Int. CL ⁶	*******************	

[56] References Cited

U.S. PATENT DOCUMENTS

3,976,302 8/1976 Hammarstrand 280/6 4,152,000 5/1979 Meisel, Jr. 280/6 4,264,014 4/1981 Hogg et al. 280/7 4,393,959 7/1983 Acker 280/7 4,705,295 11/1987 Fought 280/7 4,975,849 12/1990 Ema 280/7

FOREIGN PATENT DOCUMENTS

2654425	6/1978	Germany 280/6.12
183307	10/1983	Japan 280/754

629092 9/1978 U.S.S.R. 280/755

Primary Examiner—Eric D. Culbreth

Attorney, Agent, or Firm—Dickstein Shaprio Morin & Oshinsky LLP

[57]

ABSTRACT

Disclosed herein is a vehicle including a frame, and a stabilizer apparatus including a pressure source, first and second fluid-actuated stabilizer assemblies connected respectively to the front and rear axles shiftably moveable on the frame, one of the first and second stabilizer assemblies normally being locked against extension and contraction in the absence of pressurization thereof by the pressure source, and the other of the first and second stabilizer assemblies normally being free to extend and contract in the absence of pressurization thereof by the pressure source, a hydraulic circuit connected between the pressure source and the first and second fluid activated stabilizer assemblies and including a flow controller operable between a first mode wherein the pressure source is disconnected from the first and second stabilizer assemblies, whereby the one of the stabilizer assemblies is locked against extension and retraction, thereby locking the axle connected thereto against shifting movement relative to the frame, and whereby the other of the stabilizer assemblies is free to extend and retract, thereby permitting shifting movement relative to the frame of the axle connected thereto, and a second mode wherein the pressure source is selectively connectible to the first and second stabilizer assemblies for selective pressurization thereof by the pressure source so as to selectively extend and retract the first and second stabilizer assemblies.

19 Claims, 6 Drawing Sheets

